






FAG

B71903-C-2RSD-T-P4S-UL

Spindle bearing

Spindle bearing B719...-C-2RSD, adjusted, in pairs or sets, contact angle $\alpha = 15^\circ$, lip seals on both sides, non-contact, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Preload class	L	Preload light
Contact angle	C	Contact angle 15°
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Cage	T	Laminated fabric cage
Arrangement bearing set	U	Single bearing
Lubricant	GA21	Grease for super precision bearings, standard

Main Dimensions & Performance Data

d	17 mm	Bore diameter
D	30 mm	Outside diameter
B	7 mm	Width
C _r	5.300 N	Basic dynamic load rating, radial
C _{0r}	2.230 N	Basic static load rating, radial
C _{ur}	236 N	Fatigue load limit, radial
n _G Grease	50.000 1/min	Limiting speed for grease lubrication
≈m	2 kg	Masa



Mounting dimensions

d_a	20 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	27,5 mm	Shoulder diameter outer ring
D_a	H12	
$r_{a \max}$	0,3 mm	Maximum recess radius
$r_{a1 \max}$	0,1 mm	Maximum recess radius
a	6,6 mm	Distance between the apexes of the pressure cones

Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
$r_{1 \min}$	0,3 mm	Minimum chamfer dimension
α	15 °	Contact angle

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	80 °C	Operating temperature max.

Additional information

F_{VL}	20 N	Preload force light
F_{VM}	78 N	Preload force medium
F_{VH}	162 N	Preload force heavy
K_{aEL}	62 N	Lift-off force light
K_{aEM}	263 N	Lift-off force medium
K_{aEH}	592 N	Lift-off force heavy
c_{aL}	18 N/μm	Axial rigidity light
c_{aM}	33 N/μm	Axial rigidity medium
c_{aH}	48 N/μm	Axial rigidity heavy



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne