



FAG

**B71926-C-2RSD-T-P4S-UL**

Spindle bearing

Spindle bearing B719...-C-2RSD, adjusted, in pairs or sets, contact angle  $\alpha = 15^\circ$ , lip seals on both sides, non-contact, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

|                         |      |                                                                  |
|-------------------------|------|------------------------------------------------------------------|
| Preload class           | L    | Preload light                                                    |
| Contact angle           | C    | Contact angle 15°                                                |
| Tolerance class         | P4S  | Tolerance class P4S, FAG standard better than P4 to ISO 492:2023 |
| Cage                    | T    | Laminated fabric cage                                            |
| Arrangement bearing set | U    | Single bearing                                                   |
| Lubricant               | GA21 | Grease for super precision bearings, standard                    |

Main Dimensions & Performance Data

|                       |             |                                       |
|-----------------------|-------------|---------------------------------------|
| d                     | 130 mm      | Bore diameter                         |
| D                     | 180 mm      | Outside diameter                      |
| B                     | 24 mm       | Width                                 |
| C <sub>r</sub>        | 90.000 N    | Basic dynamic load rating, radial     |
| C <sub>0r</sub>       | 71.000 N    | Basic static load rating, radial      |
| C <sub>ur</sub>       | 6.000 N     | Fatigue load limit, radial            |
| n <sub>G Grease</sub> | 7.000 1/min | Limiting speed for grease lubrication |
| ≈m                    | 1,529 kg    | Masa                                  |



Mounting dimensions

|                     |         |                                                   |
|---------------------|---------|---------------------------------------------------|
| d <sub>a</sub>      | 139 mm  | Diameter shaft shoulder                           |
| d <sub>a</sub>      | h12     | Diameter shaft shoulder clearance                 |
| D <sub>a</sub>      | 171 mm  | Shoulder diameter outer ring                      |
| D <sub>a</sub>      | H12     |                                                   |
| r <sub>a max</sub>  | 0,6 mm  | Maximum recess radius                             |
| r <sub>a1 max</sub> | 0,6 mm  | Maximum recess radius                             |
| a                   | 32,8 mm | Distance between the apexes of the pressure cones |

Dimensions

|                    |        |                           |
|--------------------|--------|---------------------------|
| r <sub>min</sub>   | 1,5 mm | Minimum chamfer dimension |
| r <sub>1 min</sub> | 1,5 mm | Minimum chamfer dimension |
| α                  | 15 °   | Contact angle             |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 80 °C  | Operating temperature max. |

Additional information

|                   |          |                       |
|-------------------|----------|-----------------------|
| F <sub>V L</sub>  | 486 N    | Preload force light   |
| F <sub>V M</sub>  | 1.571 N  | Preload force medium  |
| F <sub>V H</sub>  | 3.160 N  | Preload force heavy   |
| K <sub>aE L</sub> | 1.488 N  | Lift-off force light  |
| K <sub>aE M</sub> | 5.171 N  | Lift-off force medium |
| K <sub>aE H</sub> | 11.084 N | Lift-off force heavy  |
| c <sub>a L</sub>  | 117 N/μm | Axial rigidity light  |
| c <sub>a M</sub>  | 197 N/μm | Axial rigidity medium |
| c <sub>a H</sub>  | 279 N/μm | Axial rigidity heavy  |



### Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne