
**FAG****B7200-E-T-P4S-UL**

Spindle bearing

Spindle bearing B72...-E, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, restricted tolerances

Informacje techniczne





Twoja aktualna wersja produktu

Preload class	L	Preload light
Contact angle	E	Contact angle 25°
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Sealing	Without	Not sealed
Cage	T	Laminated fabric cage
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	10 mm	Bore diameter
D	30 mm	Outside diameter
B	9 mm	Width
C_r	6.600 N	Basic dynamic load rating, radial
C_{0r}	2.800 N	Basic static load rating, radial
C_{ur}	305 N	Fatigue load limit, radial
n_G Grease	50.000 1/min	Limiting speed for grease lubrication
$n_{G\text{ Oil}}$	75.000 1/min	Limiting speed for oil lubrication
$\approx m$	35 g	Masa





Mounting dimensions

d _a	14,5 mm	Diameter shaft shoulder
d _a	h12	Diameter shaft shoulder clearance
D _a	25,5 mm	Shoulder diameter outer ring
D _a	H12	
r _a max	0,6 mm	Maximum recess radius
r _{a1} max	0,3 mm	Maximum recess radius
E _{tk} min	18 mm	Minimum diameter injection pitch
E _{tk} max	19,2 mm	Maximum diameter injection pitch
E _{tk1} min	18 mm	Minimum diameter injection pitch
E _{tk1} max	19,2 mm	Maximum diameter injection pitch
a	9,3 mm	Distance between the apexes of the pressure cones

Dimensions

r _{min}	0,6 mm	Minimum chamfer dimension
r ₁ min	0,6 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Additional information

F_{VL}	32 N	Preload force light
F_{VM}	141 N	Preload force medium
F_{VH}	314 N	Preload force heavy
K_{aEL}	94 N	Lift-off force light
K_{aEM}	429 N	Lift-off force medium
K_{aEH}	995 N	Lift-off force heavy
c_{aL}	36 N/μm	Axial rigidity light
c_{aM}	63 N/μm	Axial rigidity medium
c_{aH}	89 N/μm	Axial rigidity heavy

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia