

**FAG****B7206-E-T-P4S-UL**

Spindle bearing

Spindle bearing B72...-E, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Preload class	L	Preload light
Contact angle	E	Contact angle 25°
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Sealing	Without	Not sealed
Cage	T	Laminated fabric cage
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	62 mm	Outside diameter
B	16 mm	Width
C_r	22.100 N	Basic dynamic load rating, radial
C_{0r}	9.900 N	Basic static load rating, radial
C_{ur}	1.050 N	Fatigue load limit, radial
n_G Grease	22.000 1/min	Limiting speed for grease lubrication
$n_{G\text{ Oil}}$	36.000 1/min	Limiting speed for oil lubrication
$\approx m$	204 g	Masa





Mounting dimensions

d _a	37,5 mm	Diameter shaft shoulder
d _a	h12	Diameter shaft shoulder clearance
D _a	54,5 mm	Shoulder diameter outer ring
D _a	H12	
r _a max	1 mm	Maximum recess radius
r _{a1} max	0,3 mm	Maximum recess radius
E _{tk} min	41,2 mm	Minimum diameter injection pitch
E _{tk} max	43,7 mm	Maximum diameter injection pitch
E _{tk1} min	41,2 mm	Minimum diameter injection pitch
E _{tk1} max	43,7 mm	Maximum diameter injection pitch
a	18,8 mm	Distance between the apexes of the pressure cones

Dimensions

r _{min}	1 mm	Minimum chamfer dimension
r ₁ min	1 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Additional information

F_{VL}	177 N	Preload force light
F_{VM}	641 N	Preload force medium
F_{VH}	1.355 N	Preload force heavy
K_{aEL}	518 N	Lift-off force light
K_{aEM}	1.946 N	Lift-off force medium
K_{aEH}	4.271 N	Lift-off force heavy
c_{aL}	90 N/μm	Axial rigidity light
c_{aM}	148 N/μm	Axial rigidity medium
c_{aH}	203 N/μm	Axial rigidity heavy

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia