


**BE25-XL**

Radial insert ball bearing

Radial insert ball bearings BE, cylindrical outer ring, with steel aligning ring, P seals on both sides

X-life

Informacje techniczne

**Main Dimensions & Performance Data**

d	25 mm	Bore diameter
D	62 mm	Outside diameter
C _r	14.000 N	Basic dynamic load rating, radial
C _{0r}	7.800 N	Basic static load rating, radial
C _{ur}	410 N	Fatigue load limit, radial
m	0,24 kg	Masa

Dimensions

A	17 mm	Width, outer ring
C ₁	11,2 mm	Distance ring grooves
	0,2 mm	Upper distance ring groove tolerance
b	1,9 mm	Width retaining slot
	0,3 mm	Nut width upper tolerance
D ₁	59,6 mm	Diameter of groove
	-0,5 mm	Nut diameter lower tolerance

Calculation factors

f ₀	13,8	Calculation factor
----------------	------	--------------------



Additional information

205-XL-NPP-B

Bearing designation

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne



Nieosiowość statyczna