


BK0408 [🔗](#)

Drawn cup needle roller bearing closed end

Drawn cup needle roller bearings with closed end BK, to DIN 618/ISO 3245

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F _w	4 mm	Under roller diameter
D	8 mm	Outside diameter
C	8 mm	Width, outer ring
C _r	1.780 N	Basic dynamic load rating, radial
C _{0r}	1.310 N	Basic static load rating, radial
C _{ur}	147 N	Fatigue load limit, radial
n _G Grease	25.500 1/min	Limiting speed for grease lubrication
n _G	42.500 1/min	Limiting speed
n _{gr}	44.500 1/min	Reference speed
≈m	1,6 g	Masa

Dimensions

r _{min}	0,3 mm	Minimum chamfer dimension
C _{t min}	6,4 mm	Minimum width to base of drawn cup with closed end



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Additional information

GR4X8X2 Sealing ring

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mała przestrzeń zabudowy