


BK1015-B-L082

Drawn cup needle roller bearing closed end

Drawn cup needle roller bearings with closed end BK, to DIN 618/ISO 3245

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L082	Grease (L084/customer specific)
Lubrication hole	Without	
Coating	Without	
Type of Seal	Without	

Main Dimensions & Performance Data

F _w	10 mm	Under roller diameter
D	14 mm	Outside diameter
C	15 mm	Width, outer ring
C _r	6.800 N	Basic dynamic load rating, radial
C _{0r}	8.800 N	Basic static load rating, radial
C _{ur}	1.230 N	Fatigue load limit, radial
n _G Grease	14.600 1/min	Limiting speed for grease lubrication
n _G	24.300 1/min	Limiting speed
n _{gr}	18.200 1/min	Reference speed
≈m	6,2 g	Masa

Dimensions

r _{min}	0,4 mm	Minimum chamfer dimension
C _{t min}	13,4 mm	Minimum width to base of drawn cup with closed end



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Additional information

GR10X14X3	Sealing ring
G10X14X3	Sealing ring 2
IR7X10X16-XL	Suitable inner rings IR

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy