


BK2518-RS

Drawn cup needle roller bearing closed end

Drawn cup needle roller bearings with closed end BK...-RS, lip seal on one side

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L271	Grease (L271/customer specific)
Lubrication hole	Without	
Coating	Without	
Sealing	RS	Contact seal on one sides

Main Dimensions & Performance Data

F _w	25 mm	Under roller diameter
D	32 mm	Outside diameter
C	18 mm	Width, outer ring
C _r	15.600 N	Basic dynamic load rating, radial
C _{0r}	24.000 N	Basic static load rating, radial
C _{ur}	3.200 N	Fatigue load limit, radial
n _G Grease	6.100 1/min	Limiting speed for grease lubrication
n _G	6.100 1/min	Limiting speed
m	34 g	Masa

Dimensions

r _{min}	0,8 mm	Minimum chamfer dimension
C _{t min}	15,3 mm	Minimum width to base of drawn cup with closed end



Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

Additional information

LR20X25X20,5

Suitable inner rings LR

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Uszczelnienie jednostronne



Mała przestrzeń zabudowy