




CSXAA017-TV

Four-point contact bearing

Four point contact bearing, Thin section bearing CSXAA...-TV, plastic cage

Informacje techniczne



Twoja aktualna wersja produktu

Logistical code	HLE	-
Cage	TV	Plastic Cage made from PA66
Radial internal clearance	PL1	Class PL1, Normal
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	44,45 mm	Bore diameter
D	53,975 mm	Outside diameter
B	4,763 mm	Width
C _r	2.850 N	Basic dynamic load rating, radial
C _{0r}	3.100 N	Basic static load rating, radial
n _G	7.800 1/min	Limiting speed
m	20 g	Masa

Dimensions

r _{min}	0,38 mm	Minimum chamfer dimension
d ₁	48 mm	Shoulder diameter inner ring
D ₁	50,4 mm	Shoulder diameter outer ring
α	30 °	Contact angle



Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia