




E30-XL-KLL

Radial insert ball bearing

Radial insert ball bearings E...KLL, cylindrical outer ring, location by eccentric locking collar, L seals on both sides

X-life

Informacje techniczne



Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	62 mm	Outside diameter
B	36,5 mm	Width
B 1	48,5 mm	Locking collar total width
C _r	19.500 N	Basic dynamic load rating, radial
C _{0r}	11.300 N	Basic static load rating, radial
C _{ur}	590 N	Fatigue load limit, radial
≈m	0,38 kg	Masa

Dimensions

C	18 mm	Width, outer ring
C 2	20,6 mm	Sealing total width
S	18,3 mm	Distance raceway
d 1	40,2 mm	Rib diameter inner ring
D 1	52 mm	Outside diameter seal
d 3	44 mm	Outside diameter locking collar/locknut
W	4 mm	Width of flats

Calculation factors

f ₀	13,8	Calculation factor
----------------	------	--------------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne