


**E35-XL-KRR-B-L402/70-OSE**

Radial insert ball bearing

Radial insert ball bearing E...XL-KRR-B-OSE

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L402/70	L402/70
-----------	---------	---------

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D SP	72 mm	Outside diameter
B	37,7 mm	Width
C 0r	15.300 N	Basic static load rating, radial
C ur	800 N	Fatigue load limit, radial
C r	25.500 N	Basic dynamic load rating, radial
≈m	0,4 kg	Masa

Dimensions

C	19 mm	Width, outer ring
C 2	22,5 mm	Sealing total width
d 1	46,84 mm	Rib diameter inner ring
D 1	60,1 mm	Outside diameter seal

Temperature range

T min	-20 °C	Operating temperature min.
T max	100 °C	Operating temperature max.



Calculation factors

f_0	13,8	Calculation factor
-------	------	--------------------

Właściwości

-  F_r Obciążenie promieniowe
-  F_a Obciążenie osiowe jednokierunkowe
-  L_h Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna