




EGW20-E40-B [🔗](#)

Thrust washer

Thrust washer, maintenance-free, material in accordance with ISO 3547-4, with bronze backing



Informacje techniczne




Twoja aktualna wersja produktu

Maintenance	Maintenance free	
Material sliding Layer	E40	Maintenance-free sliding layer E40
Material back	B	Bronze backing

Main Dimensions & Performance Data

D _i	20 mm	Inner diameter
s ₃	1,5 mm	Wall thickness
C _a	98.500 N	Basic dynamic load rating, axial
C _{0a}	176.000 N	Basic static load rating, axial
D _o	36 mm	Outer Diameter
≈m	8,122 g	Masa



Dimensions

J	28 mm	Pitch circle
d 1	3 mm	Fixing hole diameter
t a	1 mm	Mounting dimension
d 6a	36 mm	Mounting dimension d_6a
D o UT	-0,25 mm	Outside diameter, lower tolerance
D i OT	0,25 mm	Inner diameter, upper tolerance
D i UT	0 mm	Inner diameter, lower tolerance
D o OT	0 mm	Outside diameter, upper tolerance
s 3 OT	0 mm	Wall thickness, upper tolerance
s 3 UT	-0,05 mm	Wall thickness, lower tolerance
J OT	0,12 mm	Pitch circle, upper tolerance
J UT	-0,12 mm	Pitch circle, lower tolerance
d 1 OT	0,4 mm	Fixing hole diameter, upper tolerance
d 1 UT	0,1 mm	Fixing hole diameter, lower tolerance
t a OT	0,2 mm	Mounting dimension, upper tolerance
t a UT	-0,2 mm	Mounting dimension, lower tolerance
d 6a OT	0,12 mm	Mounting dimension d_6a, upper tolerance
d 6a UT	0 mm	Mounting dimension d_6a, lower tolerance

Temperature range

T min	-200 °C	Operating temperature min.
T max	280 °C	Operating temperature max.



Właściwości

-  Obciążenie osiowe jednokierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Bez uszczelnienia
-  Ochrona przed korozją
-  Mała przestrzeń zabudowy