




GAKSL12-PS

Rod end

Corrosion-resistant rod end, with external thread, maintenance-free, sliding layer: PTFE film, DIN ISO 12240-4, dimension series K, type F, open design

Informacje techniczne



Twoja aktualna wersja produktu

Clampable	Not clampable
Grease nipples	Cannot be relubricated
Slotted	No
Thread Pitch	Left-hand thread
Maintenance	Maintenance free
Sealing	Without
Material sliding Layer	Sliding foil
Mounting bolt	External thread

Main Dimensions & Performance Data

d 2	33 mm	Outer diameter eye
C r	24.000 N	Basic dynamic load rating
C 0r	9.100 N	Basic static load rating
d	12 mm	Bore diameter bearing
D	26 mm	Outside diameter bearing
l 2	70,5 mm	Total length
B	16 mm	Width inner ring
≈m	96,5 g	Masa



Dimensions

d _k	22,2 mm	Ball diameter
d ₁	15,4 mm	Outer flange diameter inner ring
d ₃	M12	Thread size
h	54 mm	Length of thread
C ₁	12 mm	Width of the rod end
alpha	13 °	Tilt angle
l ₁	32 mm	Thread length
l ₇	16 mm	Length of the flat surface from the bearing bore centre to the shank
B _{UT}	-0,12 mm	Width inner ring , lower tolerance
B _{OT}	0 mm	Width inner ring; upper tolerance
d _T	H7	Bore diameter_bearing_tolerance
d _{UT}	0 mm	Bore diameter, lower tolerance
d _{OT}	0,018 mm	Bore diameter bearing upper tolerance
G _r	0,005 - 0,045	Radial clearance
G _{rmax}	0,045 mm	Radial clearance, maximum
G _{rmin}	0,005 mm	Radial clearance, minimum

Temperature range

T _{min}	-10 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.

Mounting dimensions

r _{1s}	0,3 mm	Smallest single chamfer dimension, inner ring
-----------------	--------	---



Właściwości



Obciążenie promieniowe



Smarowanie dożywotnie, bezobsługowe



Bez uszczelnienia



Ochrona przed korozją



Nieosiowość statyczna



Nieosiowość dynamiczna