




GAR60-DO-2RS

Rod end



Rod end with external thread, right hand thread, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-4, dimension series E, type M, sealed design

Informacje techniczne



Twoja aktualna wersja produktu

Clampable	Not clampable	
Maintenance	Maintenance required	
Lubrication nipple	DIN71412-AM6 (tapered grease nipple)	
Slotted	No	
Thread Pitch	Right-hand thread	
Sealing	2RS	Lip seals on both sides
Radial internal clearance	CN (Group N)	Normal internal clearance
Mounting	External thread	

Main Dimensions & Performance Data

C _r	318.000 N	Basic dynamic load rating, radial
C _{0r}	405.000 N	Basic static load rating, radial
d	60 mm	Bore diameter bearing
D	90 mm	Outside diameter bearing
l ₂	277,5 mm	Total length external thread head
B	44 mm	Width inner ring
d ₂	135 mm	Outer eye diameter
≈m	5,94 kg	Masa



Mounting dimensions

d ₁	66,8 mm	Outer flange diameter inner ring
----------------	---------	----------------------------------

r _{1smin}	1 mm	Edge Spacing
--------------------	------	--------------

Dimensions

d _K	80 mm	Ball diameter
----------------	-------	---------------

d ₃	M52x3	Thread size
----------------	-------	-------------

h	210 mm	Shank Length External thread rod
---	--------	----------------------------------

C ₁	38 mm	Width of the rod end
----------------	-------	----------------------

α	6 °	Tilt angle
---	-----	------------

l ₁	115 mm	Shank Length External thread head
----------------	--------	-----------------------------------

l ₇	75 mm	Distance drilling with/shaft start
----------------	-------	------------------------------------

d _{OT}	0 mm	Bore diameter bearing, upper tolerance
-----------------	------	--

d _{UT}	-0,015 mm	Bore diameter bearing, lower tolerance
-----------------	-----------	--

d _T	0,015	Bore diameter bearing, tolerance
----------------	-------	----------------------------------

B _{OT}	0 mm	Width inner ring, upper tolerance
-----------------	------	-----------------------------------

B _{UT}	-0,15 mm	Width inner ring, lower tolerance
-----------------	----------	-----------------------------------

G _r	0.043-0.12 mm	Radial Clearance
----------------	---------------	------------------

G _{rmax}	0,12 mm	Radial clearance, maximum
-------------------	---------	---------------------------

G _{rmin}	0,043 mm	
-------------------	----------	--

Temperature range

T _{min}	-30 °C	Operating temperature min.
------------------	--------	----------------------------

T _{max}	130 °C	Operating temperature max.
------------------	--------	----------------------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna