




**GE140-SW**

Spherical plain bearing

Angular contact spherical plain bearing, maintenance-free, DIN ISO 12240-2, inner ring curved surface with hard chromium coating, open design

Informacje techniczne



Twoja aktualna wersja produktu

Maintenance Maintenance free

Material sliding Layer ELGOGLIDE

Main Dimensions & Performance Data

d	140 mm	Bore diameter bearing
D	210 mm	Outside diameter bearing
T	45 mm	Height
B	42 mm	Width inner ring
C _r	1.990.000 N	Basic dynamic load rating, radial
C _{0r}	3.320.000 N	Basic static load rating, radial
≈m	6,482 kg	Masa

Mounting dimensions

r _{1smin}	2,5 mm	Edge Spacing
r _{2smin}	0,6 mm	Edge Spacing
d _{a max}	156,9 mm	Connection measure Inner ring
D _{b min}	202 mm	Connection diameter
d _{b max}	184 mm	Connection measure Inner ring
D _{a min}	171 mm	Housing Connection Diameter



Dimensions

d _K	200 mm	Ball diameter
D ₁	160,6 mm	Bore diameter of housing washer
C	42 mm	Width Outer ring
s	20 mm	Plane Surface Spacing
α	1,8 °	Tilt angle
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
d _{UT}	-0,025 mm	Bore diameter bearing, lower tolerance
D _{OT}	0 mm	Outside diameter, upper tolerance
D _{UT}	-0,03 mm	Outside diameter, lower tolerance
T _{OT}	0,35 mm	Height, upper tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
T _{UT}	-0,35 mm	Height, lower tolerance
B _{UT}	-0,5 mm	Width inner ring, lower tolerance
C _{OT}	0 mm	Width outer ring, upper tolerance
C _{UT}	-0,5 mm	Width outer ring, lower tolerance

Temperature range

T _{min}	-50 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna