


**GE16-LO-E**

## Spherical plain bearing

Standard performance Radial spherical plain bearing, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-1, dimension series W, cylindrical extensions on inner ring, open design

## Informacje techniczne



## Twoja aktualna wersja produktu

|                           |                      |                                                                    |
|---------------------------|----------------------|--------------------------------------------------------------------|
| Maintenance               | Maintenance required |                                                                    |
| Material                  | Steel                |                                                                    |
| Sealing                   | Without              |                                                                    |
| Radial internal clearance | CN (Group N)         | Normal internal clearance                                          |
| Coating                   | Durotect M           | Inner- and outer ring coated with Durotect M (Manganese Phosphate) |

## Main Dimensions &amp; Performance Data

|                 |          |                                   |
|-----------------|----------|-----------------------------------|
| d               | 16 mm    | Bore diameter bearing             |
| D               | 28 mm    | Outside diameter bearing          |
| B               | 16 mm    | Width inner ring                  |
| C <sub>r</sub>  | 17.600 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 88.000 N | Basic static load rating, radial  |
| ≈m              | 0,035 kg | Masa                              |

## Mounting dimensions

|                    |        |                               |
|--------------------|--------|-------------------------------|
| r <sub>1smin</sub> | 0,3 mm | Edge Spacing                  |
| r <sub>2smin</sub> | 0,3 mm | Edge Spacing                  |
| d <sub>a max</sub> | 20 mm  | Connection measure Inner ring |
| D <sub>a min</sub> | 23 mm  | Housing Connection Diameter   |



Dimensions

|                   |              |                                        |
|-------------------|--------------|----------------------------------------|
| C                 | 9 mm         | Width Outer ring                       |
| d <sub>K</sub>    | 23 mm        | Ball diameter                          |
| α                 | 4 °          | Tilt angle                             |
| d <sub>OT</sub>   | 0,018 mm     | Bore diameter bearing, upper tolerance |
| d <sub>UT</sub>   | 0 mm         | Bore diameter bearing, lower tolerance |
| D <sub>OT</sub>   | 0 mm         | Outside diameter, upper tolerance      |
| D <sub>UT</sub>   | -0,009 mm    | Outside diameter, lower tolerance      |
| B <sub>OT</sub>   | 0 mm         | Width inner ring, upper tolerance      |
| B <sub>UT</sub>   | -0,18 mm     | Width inner ring, lower tolerance      |
| C <sub>OT</sub>   | 0 mm         | Width outer ring, upper tolerance      |
| C <sub>UT</sub>   | -0,24 mm     | Width outer ring, lower tolerance      |
| G <sub>r</sub>    | 0,04 - 0,082 | Radial Clearance                       |
| G <sub>rmax</sub> | 0,082 mm     | Radial clearance, maximum              |
| G <sub>rmin</sub> | 0,04 mm      | Radial clearance, minimum              |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -60 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna