




GE220-AW-XL

Spherical plain bearing

Spherical plain bearing GE...-AW-A-XL, axial/
oblique, maintenance-free

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Maintenance	Maintenance free
Coating	Without
Material sliding Layer	ELGOGLIDE

Main Dimensions & Performance Data

d	220 mm	Bore diameter bearing
D	370 mm	Outside diameter bearing
T	97 mm	Height
B	82 mm	Width inner ring
C _a	8.530.000 N	Basic dynamic load rating, axial
C _{0a}	14.200.000 N	Basic static load rating, axial
≈m	45,22 kg	Masa

Mounting dimensions

r _{1smin}	1,5 mm	Edge Spacing
r _{2smin}	0,6 mm	Edge Spacing
d _{a max}	289 mm	Connection measure Inner ring
D _{a min}	279 mm	Housing Connection Diameter



Dimensions

d _K	388 mm	Ball diameter
d ₂	350 mm	Outer eye diameter
d ₃	289 mm	Front surface diameter of shaft washer
D ₁	265 mm	Bore diameter of housing washer
C	67 mm	Width Outer ring
s	75 mm	Plane Surface Spacing
α	7 °	Tilt angle
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
d _{UT}	-0,03 mm	Bore diameter bearing, lower tolerance
D _{OT}	0 mm	Outside diameter, upper tolerance
D _{UT}	-0,04 mm	Outside diameter, lower tolerance
T _{OT}	0 mm	Height, upper tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
T _{UT}	-0,6 mm	Height, lower tolerance
B _{UT}	-0,6 mm	Width inner ring, lower tolerance
C _{OT}	0 mm	Width outer ring, upper tolerance
C _{UT}	-0,6 mm	Width outer ring, lower tolerance

Temperature range

T _{min}	-50 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna