



GE260-DO-2RS

Spherical plain bearing

High performance radial spherical plain bearing, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-1, dimension series E, sealedHigh-performance: For highest load rating and lifetime demands

Informacje techniczne



Twoja aktualna wersja produktu

Maintenance	Maintenance required	
Material	Steel	
Sealing	2RS	Lip seals on both sides
Radial internal clearance	CN (Group N)	Normal internal clearance
Coating	Durotect M	Inner- and outer ring coated with Durotect M (Manganese Phosphate)

Main Dimensions & Performance Data

d	260 mm	Bore diameter bearing
D	370 mm	Outside diameter bearing
B	150 mm	Width inner ring
C _r	3.950.000 N	Basic dynamic load rating, radial
C _{0r}	15.200.000 N	Basic static load rating, radial
≈m	50,8 kg	Masa

Mounting dimensions

r ₁ min	1,1 mm	Edge Spacing
r ₂ min	1,1 mm	Edge Spacing
d _a max	288,3 mm	Connection measure Inner ring
D _a min	319 mm	Housing Connection Diameter



Dimensions

C	110 mm	Width Outer ring
d _K	325 mm	Ball diameter
α	7 °	Tilt angle
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
d _{UT}	-0,035 mm	Bore diameter bearing, lower tolerance
D _{OT}	0 mm	Outside diameter, upper tolerance
D _{UT}	-0,04 mm	Outside diameter, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
B _{UT}	-0,35 mm	Width inner ring, lower tolerance
C _{OT}	0 mm	Width outer ring, upper tolerance
C _{UT}	-0,8 mm	Width outer ring, lower tolerance
G _r	0,11 - 0,214	Radial Clearance
G _{rmax}	0,214 mm	Radial clearance, maximum
G _{rmin}	0,11 mm	Radial clearance, minimum

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	130 °C	Operating temperature max.



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Uszczelnienie dwustronne



Łożysko gabarytowe



Nieosiowość statyczna



Nieosiowość dynamiczna