


GE34-ZO-E

Spherical plain bearing

Radial spherical plain bearing, requiring maintenance, sliding contact surface: steel/ steel, inch size, open design

Informacje techniczne



Twoja aktualna wersja produktu

Maintenance	Maintenance required	
Material	Steel	
Sealing	Without	
Radial internal clearance	CN (Group N)	Normal internal clearance
Coating	Durotect M	Inner- and outer ring coated with Durotect M (Manganese Phosphate)

Main Dimensions & Performance Data

d	34,925 mm	Bore diameter bearing
D	55,563 mm	Outside diameter bearing
B	30,15 mm	Width inner ring
C _r	103.000 N	Basic dynamic load rating, radial
C _{0r}	513.000 N	Basic static load rating, radial
≈m	0,29 kg	Masa

Mounting dimensions

r ₁ min	0,6 mm	Edge Spacing
r ₂ min	1 mm	Edge Spacing
d _a max	38,6 mm	Connection measure Inner ring
D _a min	43,5 mm	Housing Connection Diameter



Dimensions

C	26,187 mm	Width Outer ring
d _K	49 mm	Ball diameter
α	6 °	Tilt angle
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
d _{UT}	-0,012 mm	Bore diameter bearing, lower tolerance
d _T	0,012	Bore diameter bearing, tolerance
D _{OT}	0 mm	Outside diameter, upper tolerance
D _{UT}	-0,013 mm	Outside diameter, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
B _{UT}	-0,12 mm	Width inner ring, lower tolerance
C _{OT}	0 mm	Width outer ring, upper tolerance
C _{UT}	0,3 mm	Width outer ring, lower tolerance
G _r	0,08 - 0,18	Radial Clearance
G _{rmax}	0,18 mm	Radial clearance, maximum
G _{rmin}	0,08 mm	Radial clearance, minimum

Temperature range

T _{min}	-60 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna