




**GE60-SW**

## Spherical plain bearing

Angular contact spherical plain bearing,  
maintenance-free, DIN ISO 12240-2, inner  
ring curved surface with hard chromium  
coating, open design

## Informacje techniczne



## Twoja aktualna wersja produktu

Maintenance Maintenance free

Material sliding Layer ELGOGLIDE

## Main Dimensions &amp; Performance Data

|                 |           |                                   |
|-----------------|-----------|-----------------------------------|
| d               | 60 mm     | Bore diameter bearing             |
| D               | 95 mm     | Outside diameter bearing          |
| T               | 23 mm     | Height                            |
| B               | 22 mm     | Width inner ring                  |
| C <sub>r</sub>  | 483.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 805.000 N | Basic static load rating, radial  |
| ≈m              | 0,72 kg   | Masa                              |

## Mounting dimensions

|                    |         |                               |
|--------------------|---------|-------------------------------|
| r <sub>1smin</sub> | 1,5 mm  | Edge Spacing                  |
| r <sub>2smin</sub> | 0,6 mm  | Edge Spacing                  |
| d <sub>a max</sub> | 66,9 mm | Connection measure Inner ring |
| D <sub>b min</sub> | 87 mm   | Connection diameter           |
| d <sub>b max</sub> | 77 mm   | Connection measure Inner ring |
| D <sub>a min</sub> | 76 mm   | Housing Connection Diameter   |



Dimensions

|                 |           |                                        |
|-----------------|-----------|----------------------------------------|
| d <sub>K</sub>  | 86 mm     | Ball diameter                          |
| D <sub>1</sub>  | 68,1 mm   | Bore diameter of housing washer        |
| C               | 22 mm     | Width Outer ring                       |
| s               | 5 mm      | Plane Surface Spacing                  |
| α               | 1,3 °     | Tilt angle                             |
| d <sub>OT</sub> | 0 mm      | Bore diameter bearing, upper tolerance |
| d <sub>UT</sub> | -0,015 mm | Bore diameter bearing, lower tolerance |
| D <sub>OT</sub> | 0 mm      | Outside diameter, upper tolerance      |
| D <sub>UT</sub> | -0,018 mm | Outside diameter, lower tolerance      |
| T <sub>OT</sub> | 0,25 mm   | Height, upper tolerance                |
| B <sub>OT</sub> | 0 mm      | Width inner ring, upper tolerance      |
| T <sub>UT</sub> | -0,25 mm  | Height, lower tolerance                |
| B <sub>UT</sub> | -0,3 mm   | Width inner ring, lower tolerance      |
| C <sub>OT</sub> | 0 mm      | Width outer ring, upper tolerance      |
| C <sub>UT</sub> | -0,3 mm   | Width outer ring, lower tolerance      |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -50 °C | Operating temperature min. |
| T <sub>max</sub> | 150 °C | Operating temperature max. |

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna