




GIHRK25-DO

Rod end

Hydraulic rod end, with thread clamping device, right hand thread, requiring maintenance, sliding contact surface: steel/ steel, open design

Informacje techniczne



Twoja aktualna wersja produktu

Clampable	Clampable	
Maintenance	Maintenance required	
Lubrication nipple	DIN71412-AM6 (tapered grease nipple)	
Slotted	Slotted, both sides	
Thread Pitch	Right-hand thread	
Sealing	Without	
Radial internal clearance	CN (Group N)	Normal internal clearance
Mounting	Internal thread	

Main Dimensions & Performance Data

C _r	62.800 N	Basic dynamic load rating, radial
C _{0r}	65.500 N	Basic static load rating, radial
d	25 mm	Bore diameter bearing
d ₂	56 mm	Outer eye diameter
l ₄	80 mm	Total length internal thread head
D	42 mm	Outside diameter bearing
B	20 mm	Width inner ring
≈m	0,49 kg	Masa



Dimensions

α	7 °	Tilt angle
C ₁	23 mm	Width of the rod end
d _K	35,5 mm	Ball diameter
d ₃	M16x1,5	Thread size
d ₄	25 mm	Shank diameter
d ₅	46 mm	Shank diameter, large
d ₇	M8x25	Diameter screw clamp
h ₁	50 mm	Shank Length Internal thread head
l ₃	17 mm	Thread length Internal thread
l ₇	25 mm	Distance drilling with/shaft start
d _{UT}	-0,01 mm	Bore diameter bearing, lower tolerance
d _T	0,01	Bore diameter bearing, tolerance
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
B _{UT}	-0,12 mm	Width inner ring, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
M _A	32 Nm	Tightening torque
G _r	0,025 - 0,1 mm	Radial Clearance
G _{rmin}	0,025 mm	Radial clearance, minimum
G _{rmax}	0,1 mm	Radial clearance, maximum

Mounting dimensions

r _{1smin}	0,6 mm	Edge Spacing
d ₁	29,3 mm	Outer flange diameter inner ring

Temperature range

T _{min}	-60 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna