


**GIKL12-PB**

Rod end



Rod end with internal thread, left hand thread,
requiring maintenance, DIN ISO 12240-4.
dimension series K, type F, open design

Informacje techniczne



Twoja aktualna wersja produktu

Clampable	Not clampable
Maintenance	Maintenance required
Lubrication nipple	DIN71412-AS6 (tapered grease nipple)
Slotted	No
Thread Pitch	Left-hand thread
Sealing	Without
Mounting	Internal thread

Main Dimensions & Performance Data

d	12 mm	Bore diameter bearing
D	26 mm	Outside diameter bearing
B	16 mm	Width inner ring
C _r	13.300 N	Basic dynamic load rating, radial
C _{0r}	20.800 N	Basic static load rating, radial
G _r	0 - 0,035	Radial Clearance
≈m	0,092 kg	Masa



Dimensions

d _K	22,225 mm	Ball diameter
d ₁	15,4 mm	Outer flange diameter inner ring
d ₂	32 mm	Outer eye diameter
d ₃	M12	Thread size
d ₄	17,5 mm	Shank diameter
h ₁	50 mm	Shank Length Internal thread head
C ₁	12 mm	Width of the rod end
α	13 °	Tilt angle
l ₃	22 mm	Thread length Internal thread
l ₄	66 mm	Total length internal thread head
l ₅	6,5 mm	Length rod end shank
l ₇	17 mm	Distance drilling with/shaft start
d ₅	22 mm	Shank diameter, large
r _{1smin}	0,3 mm	Edge Spacing
W	19 mm	Width Across Flat
d _{OT}	0,018 mm	Bore diameter bearing, upper tolerance
d _{UT}	0 mm	Bore diameter bearing, lower tolerance
d _T	H7	Bore diameter bearing, tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
B _{UT}	-0,12 mm	Width inner ring, lower tolerance
G _{rmax}	0,035 mm	Radial clearance, maximum
G _{rmin}	0 mm	Radial clearance, minimum

Temperature range

T _{min}	-60 °C	Operating temperature min.
T _{max}	250 °C	Operating temperature max.



Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna