




GIKL25-PW

Rod end



Rod end with internal thread, left hand thread, maintenance-free, sliding layer: PTFE film, brass outer ring, DIN ISO 12240-4, dimension series K, type F, open design

Informacje techniczne



Twoja aktualna wersja produktu

Clampable	Not clampable
Maintenance	Maintenance free
Lubrication nipple	Cannot be relubricated
Slotted	No
Thread Pitch	Left-hand thread
Sealing	Without
Mounting	Internal thread

Main Dimensions & Performance Data

C _r	84.800 N	Basic dynamic load rating, radial
C _{0r}	72.900 N	Basic static load rating, radial
d	25 mm	Bore diameter bearing
d ₂	60 mm	Outer eye diameter
l ₄	124 mm	Total length internal thread head
≈m	0,73 kg	Masa



Dimensions

C 1	22 mm	Width of the rod end
D	47 mm	Outside diameter bearing
B	31 mm	Width inner ring
d K	42,85 mm	Ball diameter
d 3	M24x2	Thread size
d 4	33,5 mm	Shank diameter
d 5	42 mm	Shank diameter, large
h 1	94 mm	Shank Length Internal thread head
α	15 °	Tilt angle
l 3	42 mm	Thread length Internal thread
l 5	12 mm	Length rod end shank
l 7	32 mm	Distance drilling with/shaft start
W	36 mm	Width Across Flat
d UT	0 mm	Bore diameter bearing, lower tolerance
d T	H7	Bore diameter bearing, tolerance
d OT	0,021 mm	Bore diameter bearing, upper tolerance
B UT	-0,12 mm	Width inner ring, lower tolerance
B OT	0 mm	Width inner ring, upper tolerance
G r	0 - 0,035	Radial Clearance
G rmin	0 mm	Radial clearance, minimum
G rmax	0,035 mm	Radial clearance, maximum

Mounting dimensions

r 1smin	0,3 mm	Edge Spacing
d 1	29,5 mm	Outer flange diameter inner ring



Temperature range

T _{min}	-50 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie dożywotnie, bezobsługowe
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna