




GIL60-DO-2RS

Rod end



Rod end with internal thread, left hand thread, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-4, dimension series E, type F, sealed

Informacje techniczne



Twoja aktualna wersja produktu

Clampable	Not clampable	
Maintenance	Maintenance required	
Lubrication nipple	DIN71412-AM6 (tapered grease nipple)	
Slotted	No	
Thread Pitch	Left-hand thread	
Sealing	2RS	Lip seals on both sides
Radial internal clearance	CN (Group N)	Normal internal clearance
Mounting	Internal thread	

Main Dimensions & Performance Data

d	60 mm	Bore diameter bearing
D	90 mm	Outside diameter bearing
B	44 mm	Width inner ring
C _r	318.000 N	Basic dynamic load rating, radial
C _{0r}	405.000 N	Basic static load rating, radial
G _r	0,043 - 0,12 mm	Radial Clearance
≈m	5,6 kg	Masa



Dimensions

d _K	80 mm	Ball diameter
d ₁	66,8 mm	Outer flange diameter inner ring
d ₂	135 mm	Outer eye diameter
d ₃	M52X3	Thread size
d ₄	70 mm	Shank diameter
h ₁	175 mm	Shank Length Internal thread head
C ₁	38 mm	Width of the rod end
α	6 °	Tilt angle
l ₃	70 mm	Thread length Internal thread
l ₄	242,5 mm	Total length internal thread head
l ₅	20 mm	Length rod end shank
l ₇	75 mm	Distance drilling with/shaft start
d ₅	88 mm	Shank diameter, large
r _{1smin}	1 mm	Edge Spacing
W	75 mm	Width Across Flat
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
d _{UT}	-0,015 mm	Bore diameter bearing, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
B _{UT}	-0,15 mm	Width inner ring, lower tolerance
G _{rmax}	0,12 mm	Radial clearance, maximum
G _{rmin}	0,043 mm	Radial clearance, minimum

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	130 °C	Operating temperature max.



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna