


**GRAE45-XL-NPP-B-FA125**

Radial insert ball bearing

Radial insert ball bearing GRAE...XL-NPP-B

**X-life**

## Informacje techniczne

**Main Dimensions & Performance Data**

|                 |          |                                   |
|-----------------|----------|-----------------------------------|
| d               | 45 mm    | Bore diameter                     |
| D <sub>SP</sub> | 85 mm    | Outside diameter                  |
| B               | 30,2 mm  | Width                             |
| C <sub>0r</sub> | 20.400 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 970 N    | Fatigue load limit, radial        |
| B <sub>1</sub>  | 43,8 mm  | Locking collar total width        |
| C <sub>r</sub>  | 32.500 N | Basic dynamic load rating, radial |
| ≈m              | 0,69 kg  | Masa                              |

**Dimensions**

|                |         |                                         |
|----------------|---------|-----------------------------------------|
| C              | 22 mm   | Width, outer ring                       |
| S              | 11 mm   | Distance raceway                        |
| d <sub>2</sub> | 54,3 mm | Rib diameter sealing inner ring         |
| C <sub>a</sub> | 6,4 mm  | Distance to lubrication hole            |
| d <sub>3</sub> | 63 mm   | Outside diameter locking collar/locknut |
| W              | 5 mm    | Width of flats                          |

**Calculation factors**

|                |      |                    |
|----------------|------|--------------------|
| f <sub>0</sub> | 14,1 | Calculation factor |
|----------------|------|--------------------|



### Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna