




GYE35-KRR-B-FA107-VA-FD

Radial insert ball bearing

Informacje techniczne



Main Dimensions & Performance Data

d	35 mm	Bore diameter
D _{SP}	72 mm	Outside diameter
B	42,9 mm	Width
C _{0r}	14.600 N	Basic static load rating, radial
C _{ur}	655 N	Fatigue load limit, radial
C _r	24.600 N	Basic dynamic load rating, radial
≈m	0,46 kg	Masa

Dimensions

C	20 mm	Width, outer ring
S	17,5 mm	Distance raceway
d ₁	46,9 mm	Rib diameter inner ring
C _a	5,7 mm	Distance to lubrication hole
A	6,5 mm	Distance thread
W	3 mm	Width of flats

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Calculation factors

f_0	13,8	Calculation factor
-------	------	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Ochrona przed korozją
-  Nieosiowość statyczna