



FAG

HC6232-M-C3

Deep groove ball bearing

Deep groove ball bearing HC62...-M, Hybrid bearing, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Material Bearing	HC	Hybrid bearing, rolling elements ceramic, bearing rings made of steel
Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	290 mm	Outside diameter
B	48 mm	Width
C _r	236.000 N	Basic dynamic load rating, radial
C _{0r}	250.000 N	Basic static load rating, radial
C _{ur}	6.700 N	Fatigue load limit, radial
n _G	4.850 1/min	Limiting speed
n _{gr}	3.400 1/min	Reference speed
m	14,1 kg	Masa



Mounting dimensions

$d_{a\ min}$	174 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	276 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2,5 mm	Maximum fillet radius

Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
D_1	244,95 mm	Shoulder diameter outer ring
d_1	204,94 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

f_0	18,7	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Izolowane