


**FAG****HCS71902-E-T-P4S-UL**

High speed spindle bearing

High speed spindle bearing HCS719...-E, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, with ceramic balls, lip seals on both sides, non-contact, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Preload class	L	Preload light
Contact angle	E	Contact angle 25°
Sealing	2RSD	Non-contact sealed on both sides and greased "for life"
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	15 mm	Bore diameter
D	28 mm	Outside diameter
B	7 mm	Width
C_r	2.410 N	Basic dynamic load rating, radial
C_{0r}	950 N	Basic static load rating, radial
C_{ur}	76 N	Fatigue load limit, radial
n_G Grease	85.000 1/min	Limiting speed for grease lubrication
$\approx m$	18 g	Masa



Mounting dimensions

d_a	18 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	25,5 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	0,3 mm	Maximum recess radius
$r_{a1 \max}$	0,1 mm	Maximum recess radius
a	8,5 mm	Distance between the apexes of the pressure cones

Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
$r_{1 \min}$	0,3 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	80 °C	Operating temperature max.

Additional information

F_{VL}	11 N	Preload force light
F_{VM}	32 N	Preload force medium
F_{VH}	63 N	Preload force heavy
K_{aEL}	30 N	Lift-off force light
K_{aEM}	92 N	Lift-off force medium
K_{aEH}	188 N	Lift-off force heavy
c_{aL}	28 N/μm	Axial rigidity light
c_{aM}	42 N/μm	Axial rigidity medium
c_{aH}	54 N/μm	Axial rigidity heavy



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne