



HK0608

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F_w	6 mm	Under roller diameter
D	10 mm	Outside diameter
C	8 mm	Width
C_r	2.030 N	Basic dynamic load rating, radial
C_{0r}	1.650 N	Basic static load rating, radial
C_{ur}	187 N	Fatigue load limit, radial
n_G	36.500 1/min	Limiting speed
$n_{G\text{ Grease}}$	21.900 1/min	Limiting speed for grease lubrication
n_{gr}	31.500 1/min	Reference speed
$\approx m$	2 g	Masa

Dimensions

C_1	8 mm	Width, outer ring
r_{min}	0,4 mm	Minimum chamfer dimension



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Additional information

GR6X10X2	Sealing ring
----------	--------------

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy