

**HK1012-AS1-B**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearing open end
HK...AS1-B, single row, with cage

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without	
Lubrication hole	AS1	With (1)
Coating	Without	
Sealing	Without	

Main Dimensions & Performance Data

F_w	10 mm	Under roller diameter
D	14 mm	Outside diameter
C	12 mm	Width
C_r	5.500 N	Basic dynamic load rating, radial
C_{0r}	6.800 N	Basic static load rating, radial
C_{ur}	950 N	Fatigue load limit, radial
n_G	24.300 1/min	Limiting speed
$n_{G\text{ Grease}}$	14.600 1/min	Limiting speed for grease lubrication
n_{gr}	18.400 1/min	Reference speed
$\approx m$	4,558 g	Masa

Dimensions

C_1	12 mm	Width, outer ring
$r_{\min}$	0,4 mm	Minimum chamfer dimension



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Additional information

GR10X14X3	Sealing ring
G10X14X3	Sealing ring 2
IR7X10X12-XL	Suitable inner rings IR

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Mała przestrzeń zabudowy