


HK2218-RS

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK...-RS, lip seal on one side, to DIN 618

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L271	Grease (L271/standart specific)
Lubrication hole	Without	
Coating	Without	
Sealing	RS	Contact seal on one sides

Main Dimensions & Performance Data

F _w	22 mm	Under roller diameter
D	28 mm	Outside diameter
C	18 mm	Width
C _r	13.400 N	Basic dynamic load rating, radial
C _{0r}	22.100 N	Basic static load rating, radial
C _{ur}	2.850 N	Fatigue load limit, radial
n _G	7.000 1/min	Limiting speed
n _G Grease	7.000 1/min	Limiting speed for grease lubrication
m	22,24 g	Masa

Dimensions

r _{min}	0,8 mm	Minimum chamfer dimension
------------------	--------	---------------------------

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Additional information

IR17X22X23-XL

Suitable inner rings IR

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Uszczelnienie jednostronne



Mala przestrzeń zabudowy