

**HK2516-2RS**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK...-2RS, lip seals on both sides, to DIN 618

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L271	Grease (L271/standart specific)
Lubrication hole	Without	
Coating	Without	
Sealing	2RS	Contact seal on both sides

Main Dimensions & Performance Data

F_w	25 mm	Under roller diameter
D	32 mm	Outside diameter
C_r	11.000 N	Basic dynamic load rating, radial
C_{0r}	15.200 N	Basic static load rating, radial
C_{ur}	2.030 N	Fatigue load limit, radial
n_G	6.100 1/min	Limiting speed
n_G Grease	6.100 1/min	Limiting speed for grease lubrication
$\approx m$	23,375 g	Masa

Dimensions

C_1	16 mm	Width, outer ring
r_{min}	0,8 mm	Minimum chamfer dimension

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	100 °C	Operating temperature max.



Additional information

LR20X25X16,5	Suitable inner rings LR
IR20X25X17-XL	Suitable inner rings IR

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Uszczelnienie dwustronne



Mala przestrzeń zabudowy