
**HK2516-AS1-B**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearing open end
HK...AS1-B, single row, with cage

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without	
Lubrication hole	AS1	With (1)
Coating	Without	
Sealing	Without	

Main Dimensions & Performance Data

F_w	25 mm	Under roller diameter
D	32 mm	Outside diameter
C	16 mm	Width
C_r	15.600 N	Basic dynamic load rating, radial
C_{0r}	24.000 N	Basic static load rating, radial
C_{ur}	3.200 N	Fatigue load limit, radial
n_G	10.200 1/min	Limiting speed
$n_{G\text{ Grease}}$	6.100 1/min	Limiting speed for grease lubrication
n_{gr}	7.500 1/min	Reference speed
$\approx m$	25,98 g	Masa

Dimensions

$r_{\min}$	0,8 mm	Minimum chamfer dimension
------------	--------	---------------------------



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Additional information

SD25X32X4	Sealing ring
G25X32X4	Sealing ring 2
LR20X25X16,5	Suitable inner rings LR
IR20X25X17-XL	Suitable inner rings IR

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Mała przestrzeń zabudowy