

**HK2520-AS1-B**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearing open end
HK...AS1-B, single row, with cage

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without	
Lubrication hole	AS1	With (1)
Coating	Without	
Sealing	Without	

Main Dimensions & Performance Data

F_w	25 mm	Under roller diameter
D	32 mm	Outside diameter
C	20 mm	Width
C_r	19.900 N	Basic dynamic load rating, radial
C_{0r}	33.000 N	Basic static load rating, radial
C_{ur}	4.300 N	Fatigue load limit, radial
n_G	10.200 1/min	Limiting speed
$n_{G Grease}$	6.100 1/min	Limiting speed for grease lubrication
n_{gr}	7.400 1/min	Reference speed
$\approx m$	32,936 g	Masa

Dimensions

C_1	20 mm	Width, outer ring
r_{min}	0,8 mm	Minimum chamfer dimension



Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	140 °C	Operating temperature max.

Additional information

SD25X32X4	Sealing ring
G25X32X4	Sealing ring 2
LR20X25X20,5	Suitable inner rings LR
IR20X25X20,5-XL	Suitable inner rings IR

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Mała przestrzeń zabudowy