


HK2820-2RS-AS1-L271

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK...-2RS, lip seals on both sides, to DIN 618

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L271	Grease (L271/standart specific)
Lubrication hole	AS1	With (1)
Coating	Without	
Sealing	2RS	Contact seal on both sides

Main Dimensions & Performance Data

F _w	28 mm	Under roller diameter
D	35 mm	Outside diameter
C _r	16.400 N	Basic dynamic load rating, radial
C _{0r}	26.500 N	Basic static load rating, radial
C _{ur}	3.500 N	Fatigue load limit, radial
n _G	5.500 1/min	Limiting speed
n _G Grease	5.500 1/min	Limiting speed for grease lubrication
≈m	33,63 g	Masa

Dimensions

C ₁	20 mm	Width, outer ring
r _{min}	0,8 mm	Minimum chamfer dimension

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Additional information

LR22X28X20,5	Suitable inner rings LR
IR22X28X20-XL	Suitable inner rings IR

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Uszczelnienie dwustronne



Mala przestrzeń zabudowy