


HK3018-RS

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK...-RS, lip seal on one side, to DIN 618

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L271	Grease (L271/standart specific)
Lubrication hole	Without	
Coating	Without	
Sealing	RS	Contact seal on one sides

Main Dimensions & Performance Data

F _w	30 mm	Under roller diameter
D	37 mm	Outside diameter
C	18 mm	Width
C _r	17.200 N	Basic dynamic load rating, radial
C _{0r}	29.000 N	Basic static load rating, radial
C _{ur}	3.850 N	Fatigue load limit, radial
n _G	5.200 1/min	Limiting speed
n _G Grease	5.200 1/min	Limiting speed for grease lubrication
m	34,01 g	Masa

Dimensions

r _{min}	0,8 mm	Minimum chamfer dimension
------------------	--------	---------------------------

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Additional information

LR25X30X20,5	Suitable inner rings LR
IR25X30X20-XL	Suitable inner rings IR

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Uszczelnienie jednostronne



Mala przestrzeń zabudowy