


HK3020-2RS-AS1-L271

Drawn cup needle roller bearing open end

Drawn cup needle roller bearing open end
HK...2RS-AS1, single row, with cage

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L271	Grease (L271/standart specific)
Lubrication hole	AS1	With (1)
Coating	Without	
Sealing	2RS	Contact seal on both sides

Main Dimensions & Performance Data

F_w	30 mm	Under roller diameter
D	37 mm	Outside diameter
C_r	17.200 N	Basic dynamic load rating, radial
C_{0r}	29.000 N	Basic static load rating, radial
C_{ur}	3.850 N	Fatigue load limit, radial
n_G	5.200 1/min	Limiting speed
n_G Grease	5.200 1/min	Limiting speed for grease lubrication
$\approx m$	35,91 g	Masa

Dimensions

C_1	20 mm	Width, outer ring
r_{min}	0,8 mm	Minimum chamfer dimension

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	100 °C	Operating temperature max.



Additional information

LR25X30X20,5	Suitable inner rings LR
IR25X30X20-XL	Suitable inner rings IR

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Uszczelnienie dwustronne



Mala przestrzeń zabudowy