



HK3512

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F_w	35 mm	Under roller diameter
D	42 mm	Outside diameter
C	12 mm	Width
C_r	13.100 N	Basic dynamic load rating, radial
C_{0r}	21.300 N	Basic static load rating, radial
C_{ur}	2.850 N	Fatigue load limit, radial
n_G	7.500 1/min	Limiting speed
$n_{G Grease}$	4.500 1/min	Limiting speed for grease lubrication
n_{gr}	5.800 1/min	Reference speed
$\approx m$	26,07 g	Masa

Dimensions

C_1	12 mm	Width, outer ring
r_{min}	0,8 mm	Minimum chamfer dimension



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Additional information

SD35X42X4	Sealing ring
G35X42X4	Sealing ring 2
LR30X35X12,5	Suitable inner rings LR
IR30X35X13-XL	Suitable inner rings IR

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Mala przestrzeń zabudowy