


HK3518-RS

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK..-RS, lip seal on one side, to DIN 618

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L271	Grease (L271/standart specific)
Lubrication hole	Without	
Coating	Without	
Sealing	RS	Contact seal on one sides

Main Dimensions & Performance Data

F _w	35 mm	Under roller diameter
D	42 mm	Outside diameter
C	18 mm	Width
C _r	18.700 N	Basic dynamic load rating, radial
C _{0r}	33.500 N	Basic static load rating, radial
C _{ur}	4.450 N	Fatigue load limit, radial
n _G	4.500 1/min	Limiting speed
n _G Grease	4.500 1/min	Limiting speed for grease lubrication
m	38,62 g	Masa

Dimensions

r _{min}	0,8 mm	Minimum chamfer dimension
------------------	--------	---------------------------

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Additional information

LR30X35X20,5	Suitable inner rings LR
IR30X35X20-XL	Suitable inner rings IR

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Uszczelnienie jednostronne
-  Mała przestrzeń zabudowy