

**HK50X57X16**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearing open end
HK, single row, with cage

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F_w	50 mm	Under roller diameter
D	57 mm	Outside diameter
C	16 mm	Width
C_r	18.200 N	Basic dynamic load rating, radial
C_{0r}	36.500 N	Basic static load rating, radial
C_{ur}	4.700 N	Fatigue load limit, radial
n_G	5.300 1/min	Limiting speed
$n_{G\text{ Grease}}$	3.200 1/min	Limiting speed for grease lubrication
n_{gr}	4.350 1/min	Reference speed
$\approx m$	54,3 g	Masa

Dimensions

C_1	16 mm	Width, outer ring
$r_{\min}$	0,8 mm	Minimum chamfer dimension



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy