


HN2520 [↗](#)

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HN, full complement needle roller set

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L563	Grease (L563/standart specific)
-----------	------	---------------------------------

Main Dimensions & Performance Data

F_w	25 mm	Under roller diameter
D	32 mm	Outside diameter
C	20 mm	Width, outer ring
C_r	28.000 N	Basic dynamic load rating, radial
C_{0r}	59.000 N	Basic static load rating, radial
C_{ur}	8.000 N	Fatigue load limit, radial
n_G Grease	4.350 1/min	Limiting speed for grease lubrication
n_{gr}	5.800 1/min	Reference speed
$\approx m$	40 g	Masa

Dimensions

r_{min}	0,8 mm	Minimum chamfer dimension
-----------	--------	---------------------------

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	140 °C	Operating temperature max.

Additional information

IR20X25X20-XL	Suitable inner rings IR
LR20X25X20,5	Suitable inner rings LR



Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mala przestrzeń zabudowy