






FAG

HSS7001-E-T-P4S-UL

High speed spindle bearing

High speed spindle bearing HSS70...-E, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, lip seals on both sides, non-contact, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Contact angle	E	Contact angle 25°
Sealing	2RSD	Non-contact sealed on both sides and greased "for life"
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing
Preload class	L	Preload light
Lubricant	GA21	Grease for super precision bearings, standard

Main Dimensions & Performance Data

d	12 mm	Bore diameter
D	28 mm	Outside diameter
B	8 mm	Width
C _r	2.320 N	Basic dynamic load rating, radial
C _{0r}	910 N	Basic static load rating, radial
C _{ur}	97 N	Fatigue load limit, radial
n _G Grease	75.000 1/min	Limiting speed for grease lubrication
n _G	110.000 1/min	Limiting speed

≈m 25 g Masa



Mounting dimensions

d_a	16,5 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	24,5 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a\ max}$	0,3 mm	Maximum recess radius
$r_{a1\ max}$	0,1 mm	Maximum recess radius
a	8,7 mm	Distance between the apexes of the pressure cones

Dimensions

r_{min}	0,3 mm	Minimum chamfer dimension
$r_{1\ min}$	0,3 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	80 °C	Operating temperature max.

Additional information

F_{VL}	15 N	Preload force light
F_{VM}	44 N	Preload force medium
F_{VH}	88 N	Preload force heavy
K_{aEL}	43 N	Lift-off force light
K_{aEM}	131 N	Lift-off force medium
K_{aEH}	268 N	Lift-off force heavy
c_{aL}	27 N/μm	Axial rigidity light
c_{aM}	40 N/μm	Axial rigidity medium
c_{aH}	53 N/μm	Axial rigidity heavy



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne