




FAG

HSS71915-C-T-P4S-UL

High speed spindle bearing

High speed spindle bearing HSS719...-C, adjusted, in pairs or sets, contact angle $\alpha = 15^\circ$, lip seals on both sides, non-contact, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Contact angle	C	Contact angle 15°
Sealing	2RSD	Non-contact sealed on both sides and greased "for life"
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing
Preload class	L	Preload light
Lubricant	GA21	Grease for super precision bearings, standard

Main Dimensions & Performance Data

d	75 mm	Bore diameter
D	105 mm	Outside diameter
B	16 mm	Width
C _r	18.300 N	Basic dynamic load rating, radial
C _{0r}	13.800 N	Basic static load rating, radial
C _{ur}	1.460 N	Fatigue load limit, radial
n _G Grease	18.000 1/min	Limiting speed for grease lubrication
n _G	28.000 1/min	Limiting speed
≈m	355 g	Masa



Mounting dimensions

d _a	81 mm	Diameter shaft shoulder
d _a	h12	Diameter shaft shoulder clearance
D _a	99,5 mm	Shoulder diameter outer ring
D _a	H12	Shoulder diameter outer ring clearance
r _{a max}	0,6 mm	Maximum recess radius
r _{a1 max}	0,3 mm	Maximum recess radius
a	20,1 mm	Distance between the apexes of the pressure cones

Dimensions

r _{min}	1 mm	Minimum chamfer dimension
r _{1 min}	1 mm	Minimum chamfer dimension
α	15 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.

Additional information

F _{V L}	64 N	Preload force light
F _{V M}	191 N	Preload force medium
F _{V H}	382 N	Preload force heavy
K _{aE L}	190 N	Lift-off force light
K _{aE M}	597 N	Lift-off force medium
K _{aE H}	1.242 N	Lift-off force heavy
c _{a L}	50 N/μm	Axial rigidity light
c _{a M}	78 N/μm	Axial rigidity medium
c _{a H}	106 N/μm	Axial rigidity heavy



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne