



**HXPM-50T-2/3-ARM-LONG**

Mobile hydraulic heavy duty hook puller

BETEX HXPM, 2/3-arm self-centering, max. pull-off force 490 kN, long version, mobile

Informacje techniczne

Twoja aktualna wersja produktu

|        |      |           |
|--------|------|-----------|
| Series | HXPM | With cart |
|--------|------|-----------|

Technical data

|          |                   |                                                           |
|----------|-------------------|-----------------------------------------------------------|
| U        | 230 V             | Voltage                                                   |
|          | AC power          | Current type                                              |
| f        | 50 – 60 Hz        | Power frequency                                           |
| s cm max | 330 mm            | Max. working stroke main cylinder                         |
| p max    | 700 bar           | Max. operating pressure                                   |
| w min    | 200 mm            | Grip width, min.                                          |
| w max    | 1.250 mm          | Grip width, max.                                          |
| t max    | 780 mm            | Grip depth, max.                                          |
| F p      | 490 kN            | Pulling force                                             |
|          | 820 – 1370        | Working height range [bottom – center axis cylinder] (mm) |
|          | 2545 x 800 x 1155 | Dimensions [LxWxH] (mm)                                   |
| ≈m       | 400 kg            | Masa                                                      |



Additional information

|                                                                                                                                                                             |                      |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
| electrically operated hydraulic unit for main cylinder and height adjustment, safety valve prevents overload, opening and closing of the gripper arms by means of hand pump | Functional principle |
| two- or three-arm puller (convertible)                                                                                                                                      | Usability            |
| 2 swivel castors with brake function, 2 fixed castors                                                                                                                       | Castors              |
| Remote control, 4 adapter pieces (total length 620 mm), security blanket                                                                                                    | Included in delivery |