




HYDNUT395-E

Hydraulic nut

HYDNUT..-E

Informacje techniczne



Twoja aktualna wersja produktu

|        |   |                                           |
|--------|---|-------------------------------------------|
| Series | E | Metric fine pitch thread/trapezoid thread |
|--------|---|-------------------------------------------|

Technical data

|     |           |                      |
|-----|-----------|----------------------|
| d   | Tr395x5   | Thread               |
| D   | 512 mm    | Outer Diameter       |
| B   | 67 mm     | Width                |
| b   | 56 mm     | Width press ring     |
| D 1 | 470 mm    |                      |
| d 1 | 397 mm    |                      |
| s   | 17 mm     | Stroke, max.         |
|     | 356,1 cm² | Piston surface       |
|     | 500 bar   | Pressure, max.       |
|     | 1.780 kN  | Drive-up force, max. |
| ≈m  | 44,3 kg   | Masa                 |

Additional information

|                                                                                                                                                                                                              |                |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| 1 pc. Hydraulic nut,<br>3 pcs. Clamping screws,<br>1 pc. Screw plug,<br>1 pc. Connection nipple,<br>3 pcs. to 5 pcs. Threaded pins,<br>1 pc. Hand lever,<br>1 pc. Replacement seal set,<br>1 pc. User manual | Delivery scope |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|