



K25X29X10

Needle roller cage assembly

Needle roller cage assembly K, single row

Informacje techniczne



Twoja aktualna wersja produktu

|      |    |                   |
|------|----|-------------------|
| Cage | JN | Steel sheet metal |
|------|----|-------------------|

Main Dimensions & Performance Data

|                 |              |                                              |
|-----------------|--------------|----------------------------------------------|
| F <sub>w</sub>  | 25 mm        | Inner diameter of needle roller complement   |
| E <sub>w</sub>  | 29 mm        | Outside diameter of needle roller complement |
| B <sub>c</sub>  | 10 mm        | Width                                        |
| C <sub>r</sub>  | 9.900 N      | Basic dynamic load rating, radial            |
| C <sub>0r</sub> | 15.400 N     | Basic static load rating, radial             |
| C <sub>ur</sub> | 1.960 N      | Fatigue load limit, radial                   |
| n <sub>G</sub>  | 18.100 1/min | Limiting speed                               |
| n <sub>gr</sub> | 10.200 1/min | Reference speed                              |
| m               | 6,8 g        | Masa                                         |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 140 °C | Operating temperature max. |



### Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mala przestrzeń zabudowy