



K35X45X30

Needle roller cage assembly

Needle roller cage assembly K, single row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	JN	Steel sheet metal
------	----	-------------------

Main Dimensions & Performance Data

F _w	35 mm	Inner diameter of needle roller complement
----------------	-------	--

E _w	45 mm	Outside diameter of needle roller complement
----------------	-------	--

B _c	30 mm	Width
----------------	-------	-------

C _r	53.000 N	Basic dynamic load rating, radial
----------------	----------	-----------------------------------

C _{0r}	79.000 N	Basic static load rating, radial
-----------------	----------	----------------------------------

C _{ur}	10.700 N	Fatigue load limit, radial
-----------------	----------	----------------------------

n _G	12.300 1/min	Limiting speed
----------------	--------------	----------------

n _{gr}	6.700 1/min	Reference speed
-----------------	-------------	-----------------

≈m	85,6 g	Masa
----	--------	------

Temperature range

T _{min}	-30 °C	Operating temperature min.
------------------	--------	----------------------------

T _{max}	140 °C	Operating temperature max.
------------------	--------	----------------------------



Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mala przestrzeń zabudowy