




K4X7X10-TV

Needle roller cage assembly

Needle roller cage assembly K..-TV, single row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------

Main Dimensions & Performance Data

F _w	4 mm	Inner diameter of needle roller complement
----------------	------	--

E _w	7 mm	Outside diameter of needle roller complement
----------------	------	--

B _c	10 mm	Width
----------------	-------	-------

C _r	2.330 N	Basic dynamic load rating, radial
----------------	---------	-----------------------------------

C _{0r}	1.840 N	Basic static load rating, radial
-----------------	---------	----------------------------------

C _{ur}	241 N	Fatigue load limit, radial
-----------------	-------	----------------------------

n _G	42.500 1/min	Limiting speed
----------------	--------------	----------------

n _{gr}	59.000 1/min	Reference speed
-----------------	--------------	-----------------

≈m	0,714 g	Masa
----	---------	------

Temperature range

T _{min}	-20 °C	Operating temperature min.
------------------	--------	----------------------------

T _{max}	120 °C	Operating temperature max.
------------------	--------	----------------------------



Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mala przestrzeń zabudowy