





K5X8X8-TV

Needle roller cage assembly

Needle roller cage assembly K..-TV, single row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------

Main Dimensions & Performance Data

F _w	5 mm	Inner diameter of needle roller complement
----------------	------	--

E _w	8 mm	Outside diameter of needle roller complement
----------------	------	--

B _c	8 mm	Width
----------------	------	-------

C _r	2.350 N	Basic dynamic load rating, radial
----------------	---------	-----------------------------------

C _{0r}	1.920 N	Basic static load rating, radial
-----------------	---------	----------------------------------

C _{ur}	242 N	Fatigue load limit, radial
-----------------	-------	----------------------------

n _G	39.000 1/min	Limiting speed
----------------	--------------	----------------

n _{gr}	48.000 1/min	Reference speed
-----------------	--------------	-----------------

≈m	0,7 g	Masa
----	-------	------

Temperature range

T _{min}	-20 °C	Operating temperature min.
------------------	--------	----------------------------

T _{max}	120 °C	Operating temperature max.
------------------	--------	----------------------------



Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mala przestrzeń zabudowy