





K7X9X7-TV

Needle roller cage assembly

Needle roller cage assembly K..-TV, single row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------

Main Dimensions & Performance Data

F _w	7 mm	Inner diameter of needle roller complement
----------------	------	--

E _w	9 mm	Outside diameter of needle roller complement
----------------	------	--

B _c	7 mm	Width
----------------	------	-------

C _r	1.680 N	Basic dynamic load rating, radial
----------------	---------	-----------------------------------

C _{0r}	1.700 N	Basic static load rating, radial
-----------------	---------	----------------------------------

C _{ur}	207 N	Fatigue load limit, radial
-----------------	-------	----------------------------

n _G	35.500 1/min	Limiting speed
----------------	--------------	----------------

n _{gr}	40.500 1/min	Reference speed
-----------------	--------------	-----------------

≈m	380,062 mg	Masa
----	------------	------

Temperature range

T _{min}	-20 °C	Operating temperature min.
------------------	--------	----------------------------

T _{max}	120 °C	Operating temperature max.
------------------	--------	----------------------------



Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mala przestrzeń zabudowy